



Mobile Information Device Programming (8)

Lecturer: Alireza Mousavi
School of Engineering & Design
www.brunel.ac.uk/~emstaam



StringItem

- A **StringItem** displays a static label or text message
- A **StringItem** does not recognise events, it therefore cannot be edited.
- You can use the *getText()* or *setText()* methods inherited for the **Item** class



Example Changing Label and Message Text E8.1

- Create a Java file called *myLabelText.java*
- Create a *Display*, *Form*, *StringItem*, and two *Command* "Exit" and "Next"
- Use the *setLabel()* and *setText()* methods to set the text:

```
siUser.setLabel("My Number: ");  
siUser.setText("123");
```



Result





Some more explanation

- In the constructor *myLabelText* we define a **StringItem** that contains a label and a text
- We also added a Command *cmNext* which invoked a call to `CommandAction()`, where we change the label and the text.



Another way

- You can directly *append* a **String** to a Form.
- There are no Labels like **StringItem** associated with the text

Method Example: *msgID = fmMain.append("User Id: "John_Smith")*



Example E8.2

- Create a *StringText.java* file
- Create a *Display, Form, 2 Commands "Next" and "Exit"*,
- Create two integers *int msgIndex, count*
- Append a string text *"UserId: JohnSmith"* to the Form: `msgIndex = fmMain.append("UserId: JohnSmith");`
- In your `commandAction(Command c, Displayable s){ ...}` you will have two options


E8.2 cont.



```
public void commandAction(Command c, Displayable s){
    if(c == cmNext){ // check if the chosen command is Next
        if( count++ == 0){ // and check if loop counter is 0
            /* -----
               option 1
               This is the first Time through this method*/
            StringItem tmpItem = (StringItem) fmMain.get(msgIndex);
            System.out.println("tmpItem.getText(): " + tmpItem.getLabel());
            // inherited from item class
            tmpItem.setLabel("Account #: ");
            tmpItem.setText("222");
        }
        else {
            /* Option 2
               Second time through this method*/
            fmMain.set(msgIndex, new StringItem("passWord: ", "letmein"));
            // Remove the Next command
            fmMain.removeCommand(cmNext);
        }
    }
    else if (c == cmExit){
        destroyApp(false);
        notifyDestroyed();
    }
}
```



Result



```
J2ME Wireless Toolkit - Example7_6  
File Edit Project Help  
New Project ... Open Project ... Settings ... Build Run Clear Console  
Device: DefaultColorPhone  
Project "Example7_6" loaded  
Project settings saved  
Building "Example7_6"  
Build complete  
Running with storage root DefaultColorPhone  
tmpItem.getText(): null  
tmpItem.getText(): Userid: JohnSmith  
tmpItem.getText(): null  
tmpItem.getText(): Userid: JohnSmith
```



TextField

- A **TextField** provides constraints on the data that a user can enter
- The code behind a **TextField** can help with limiting the characters that can be used
- In addition to character constraints **TextField** i.e. number of acceptable characters



TextField Constraints

Value	Description
Constraint_Mask	Used to determine the current value of the constrain
ANY	Allows any Character
EMAILADDR	Allows only valid email Characters
NUMERIC	Allows only numeric values
PASSWORD	Masks all characters to allow privacy
PHONENUMBER	Allows characters valid for phone numbers
URL	Allows only characters valid to point to a URL



TextField cont.

```
TfPwd = new TextField("Password: ", " ", 10, TextField.ANY |  
    TextField.PASSWORD);
```

```
tfPhone = new TextField("Phone No:", " ", 15, TextField.PHONENUMBER);
```